



700 Series

& Model 870SS Hot Water Pressure Washers

North America's #1 Manufacturer of High-Quality Cleaning Equipment

Electric / Direct or Belt Drive

Simple, easy-to-use control panel includes high-limit temperature control with precision safety controls

Pressure-relief valve protects the machine and user

Stainless-steel coil skin provides extra durability to withstand the elements

5 HP, 230V, 1PH electric motor comes with thermal overload protection and manual reset

50-ft. length of high-pressure hose for ease in cleaning around a large area

Convenient hose-reel bracket accepts swivel or stationary reels for ease in hose maneuverability and storage (optional on gas fired models)

Upright, oil fired burner delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil

Adjustable upstream detergent injection ensures high-pressure sudsing for better cleaning

Built-in wand holder provides convenient storage



Hotsy triplex, positive-displacement pump carries seven-year crankcase and lifetime manifold warranties

Model 870SS: 3.5 GPM @ 2000 PSI; 230V, 1PH; 1725 RPM Direct Drive Pump

Rust-proof, removable, non-contaminating polyethylene fuel tank includes fuel gauge in cap

37-ft. power cord with safety Ground Fault Circuit Interrupter (GFCI breaker)

Pneumatic wheels for easy maneuvering

Adjustable spray-angle nozzle with 0° to 80° spray patterns adjusts easily under high pressure

Model 770SS: 2.8 GPM @ 1500 PSI; 208-230V, 1PH; Oil Fired; 1725 RPM Direct Drive Pump



Model 771 (Propane): 2.8 GPM @ 1500 PSI; 208-230V, 1PH; 1725 RPM Direct Drive Pump. Model 772-Natural Gas (Above model shown with optional Portagear Kit & Vapor LP Tank)



Model 795SS: 3.5 GPM @ 2000 PSI; Oil fired; 230V, 1PH; 1490 RPM Belt Drive Pump

FEATURES

- 2.8 to 3.5 GPM @ 1500 to 2000 PSI
- Oil Fired, LP or Natural Gas Fired Burners
- 208V-230V, 1PH; 208V or 230V, 1PH
- Direct or Belt Drive Pumps

www.Hotsy.com

Nothing Cleans Like A Hotsy!

700 SERIES Hot-Water ELECTRIC Models

■ Oil Fired, LP or Natural Gas Fired ■ 2.8 to 3.5 GPM @ 1500 to 2000 PSI ■ Hotsy 7-Year Pump Warranty ■ Direct or Belt Drive

Designed for tough, industrial cleaning.

SPECIFICATIONS

BELT or DIRECT DRIVE

MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	PUMP	PUMP RPM	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
770SS	2.8	1500	3	1725	208-230/1	20	Oil	Hotsy Triplex	1725	Direct	Std	50'	435
771	2.8	1500	3	1725	208-230/1	13	LP	Hotsy Triplex	1725	Direct	Optional	50'	415
772	2.8	1500	3	1725	208-230/1	13	NG	Hotsy Triplex	1725	Direct	NA	50'	415
790SS	2.8	2000	4TEFC*	1725	230/1	20	Oil	Hotsy Triplex	1330	Belt	Std	50'	460
790SS-208	2.8	2000	4TEFC*	1725	208/1	22	Oil	Hotsy Triplex	1330	Belt	Std	50'	460
795SS	3.5	2000	5	3450	230/1	24	Oil	Hotsy Triplex	1490	Belt	Std	50'	500
795SS-208	3.5	2000	5	3450	208/1	27	Oil	Hotsy Triplex	1490	Belt	Std	50'	500
870SS	3.5	2000	5	1725	230/1	17	Oil	Hotsy Triplex	1725	Direct	Std	50'	475

*Totally enclosed fan cooled (TEFC)



Clean better with Hotsy detergents

Hotsy pressure washers clean best when matched with our specially-formulated Hotsy detergents. Nearly all 40 Hotsy detergent formulations contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

Spend some time with a Hotsy Expert

Hotsy has more than 130 local Sales & Service Distributors in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Rely on our network of seasoned service professionals for the safest, most effective and most efficient solution to your specific cleaning need.



OPTIONS for 700 SERIES

- **10" Natural Gas or LP-Gas-Fired Draft Diverters** (Models 771 & 772) prevent backdrafts; keeps cold air out & prevents water from running down vent pipes
- **8" Oil-Fired Draft Dampener** (Models 770SS, 790SS, 795SS & 870SS) barometric; prevent backdrafts; keeps cold air out
- **Portagear** (Model 771-Propane) for easy movement around the shop
- **Propane Tank** (Model 771-Propane) Vapor LP Tank
- **Hose Reel Bracket** (Models 771&772) accepts stationary or swivel hose reels

Hotsy Accessories customize your application for top performance

Telescoping wands extend to 24' to reach high places without scaffolding



360° Pivot and non-pivot hose reels keep hose neatly stored and shop areas safe



High-pressure turbo nozzles for faster cleaning



Heavy-duty, high-pressure hoses in lengths up to 150-ft.



Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping

Distributed by:

hotsy Nothing Cleans Like a Hotsy!

Tel: (800) 525-1976 Fax: (888) 880-9631
 www.Hotsy.com email: info@Hotsy.com
 P/N 97-0473 Effective 4/05 Specifications & product descriptions subject to change without notice. ©2005 Hotsy



NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ± 5% of listed specifications.